

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SolidLux 
Instant Coating

Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SolidLux Base Coat 800

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified use: Paints and lacquers, for further details check Product Data Sheet/ Label. Uses advised against: On substrates not mentioned in the Product Data Sheet/ Label.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Lowland Coatings International B.V.

Street : Russenweg 14

Postal code/city : 8041 AL ZWOLLE

Telephone : +31 (0)38-4291200

Telefax : +31 (0)38-4210414

Contact : MSDS@wijzonol.com

1.4 Emergency telephone number

+31 (0)38-4291100(During office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

Glycerol polypropylene glycol ether (1:3), acrylate, adipate ; CAS No. : 73378-73-1

Trimethylolpropane Ethoxytriacyrylate ; CAS No. : 28961-43-5

Phenylbis(2,4,6,-trimethylbenzoyl)-phosfineoxide ; CAS No. : 162881-26-7

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/ container according to national/ international regulations.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

This mixture does not contain any substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

Hazardous ingredients

Glycerol polypropylene glycol ether (1:3), acrylate, adipate ; CAS No. : 73378-73-1

Weight fraction : $\geq 25 - < 30$ %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

3-methyl 1,5 pentanediol diacrylate ; EC No. : 264-727-7; CAS No. : 64194-22-5

Weight fraction : $\geq 10 - < 15$ %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

Trimethylolpropane Ethoxytriacrylate ; REACH registration No. : 01-2119489900-30 ; CAS No. : 28961-43-5

Weight fraction : $\geq 10 - < 15$ %

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319

Phenylbis(2,4,6-trimethylbenzoyl)-phosphineoxide ; EC No. : 423-340-5; CAS No. : 162881-26-7

Weight fraction : $\geq 1 - < 5$ %

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Chronic 4 ; H413

TOLUENE ; REACH registration No. : 01-2119471310-51 ; EC No. : 203-625-9; CAS No. : 108-88-3

Weight fraction : $< 0,5$ %

Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 Repr. 2 ; H361d STOT RE 2 ; H373 Skin Irrit. 2 ; H315 STOT SE 3 ; H336

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Rinse cautiously with water for several minutes. Remove contact lenses, if present

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO₂) Extinguishing powder Water mist

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Exposure to decomposition products may cause a health hazard. Use suitable breathing apparatus.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Avoid breathing vapours. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Comply with the health and safety at work laws.

Protective measures

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Environmental precautions

Do not allow to enter drains or water courses.

Specific requirements or handling rules

Never use pressure to empty container.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8).

7.2 Conditions for safe storage, including any incompatibilities

Packaging materials

Always keep in containers of same material as the original one. Keep container tightly closed. No smoking. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Requirements for storage rooms and vessels

Only allow access to authorised staff.

Hints on joint storage

Do not store together with

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : STEL (EC)

Limit value : 100 ppm / 384 mg/m³

Remark : H

Version : 07-02-2006

Limit value type (country of origin) : TWA (EC)

Limit value : 50 ppm / 192 mg/m³

Remark : H

Version : 07-02-2006

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye/face protection

Use safety eyewear designed to protect against splash of liquids.

Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hand protection

Use chemical-resistant gloves (according to EN 374).

By short-term hand contact : For short-term contact use gloves with adequate chemical protection, thickness \geq 0.2 mm, performance level \geq 1 (breakthrough time \geq 10 minutes).

By long-term hand contact : For prolonged and repeated contact use gloves with adequate chemical protection, thickness 0.4 mm, performance level 6 (breakthrough time \geq 480 minutes).

Suitable material : NBR (Nitrile rubber)

Additional hand protection measures : Always ensure that gloves are free from defects and that they are stored and used correctly. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. After contact with skin, wash immediately with plenty of water and soap.

Respiratory protection

Not applicable.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety relevant basis data

Physical state :				liquid	
Odeur:				Typical paint odour.	
Odeur threshold:				Unknown	
pH :				No data available	
Melting point/melting range :				No data available	
Initial boiling point and boiling range :	(1013 hPa)			No data available	
Lower explosion limit :				0,6	Vol-%
Upper explosion limit :				No data available	
Vapour pressure :	(50 °C / 122 °F)	<		3	hPa
Vapour density:				No data available	
Density :	(20 °C / 68 °F)	approx.		1,23	g/cm ³
Solvent separation test :	(20 °C / 68 °F)			No data available	
Ignition temperature :				No data available	
Decomposition temperature :				No data available	
Viscositeit KU :	(20 °C / 68 °F)			No data available	
Flow time :	(20 °C / 68 °F)	>		90	s
Evaporation rate (n-butylacetate = 1):				No data available	DIN 53170
Flash point :		>		100	°C
Flammability:				Technically impossible.	
Explosive properties:				None	
Solubility:				No data available	
Oxidising properties:				None	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Carbon monoxide Nitrogen oxides (NOx).

SECTION 11: Toxicological information

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of Regulation (EC) 1272/2008 and not classified.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

11.1 Information on toxicological effects

The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

Do not allow to enter drains or water courses. Wastes and emptied containers should be classified in accordance with local/regional/national/international regulations.

13.1 Waste treatment methods

No information available.

13.2 Additional information

Empty containers must be scrapped or reconditioned. Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society of Testing and Materials (US)
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EWC = European Waste Catalogue
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
MRL = Maximum Residue Limit
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
OEL = Occupational Exposure Limits
PBT = Persistent, Bioaccumulative or Toxic
PNEC = Previsible Non Effect Concentration
STEL = Short-Term Exposure Limit
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Base Coat 800
Revision date : 08-11-2016
Print date : 26-11-2018

Version : 1.0.0

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
