according to Regulation (EC) No. 1907/2006 (REACH)



SolidLux Top Coat 810 AS Trade name:

Revision date: 09-11-2016 Version (Revision): 1.1.0 (1.0.0)

Print date: 26-11-2018

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SolidLux Top Coat 810 AS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified use: Paints and lacquers, for further details check Product Data Sheet/ Label. Uses advised against: On substrates not mentioned in the Product Data Sheet/ Label.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Lowland Coatings International B.V.

Street: Russenweg 14

Postal code/city: 8041 AL ZWOLLE **Telephone:** +31 (0)38-4291200 **Telefax:** +31 (0)38-4210414 Contact: MSDS@wijzonol.com 1.4 Emergency telephone number

+31 (0)38-4291100(During office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation.

Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

STOT SE 3; H335 - STOT-single exposure: Category 3; May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

Pentanoic acid, 5,5',5"-[(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tris(6,1-hexanediyliminocarbonyloxy)] tris-,

tris[2-[(1-oxo-2- propenyl)oxy]ethyl] ester; CAS No.: 478688-48-1

Trimethylolpropane Ethoxytriacrylate; CAS No.: 28961-43-5

Phenylbis(2,4,6,-trimethylbenzoyl)-phosfineoxide; CAS No.: 162881-26-7

2-Propenoic acid; CAS No.: 1245638-61-2

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Page: 1/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 810 AS

Revision date: 09-11-2016 **Version (Revision):** 1.1.0 (1.0.0)

Print date : 26-11-2018

H335 May cause respiratory irritation.

Precautionary statements

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/ container according to national/ international regulations.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

This mixture does not contain any substances presenting a health or environmental hazard within the meaning of Regulation (EC) No. 1272/2008, assigned a Community workplace exposure limit, classified as PBT/vPvB or included in the Candidate List.

Hazardous ingredients

Pentanoic acid, 5,5',5"-[(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tris(6,1-hexanediyliminocarbonyloxy)] tris-,

tris[2-[(1-oxo-2- propenyl)oxy]ethyl] ester; CAS No.: 478688-48-1

Weight fraction : \geq 30 - < 35 %

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335

3-methyl 1,5 pentanediol diacrylate; EC No.: 264-727-7; CAS No.: 64194-22-5

Weight fraction : \geq 20 - < 25 %

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Eye Irrit. 2; H319

Trimethylolpropane Ethoxytriacrylate; REACH registration No.: 01-2119489900-30; CAS No.: 28961-43-5

Weight fraction : \geq 10 - < 15 %

Classification 1272/2008 [CLP]: Skin Sens. 1; H317 Eye Irrit. 2; H319

ACRYLIC RESIN ; CAS No. : --

Weight fraction : \geq 1 - < 5 % Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Phenylbis(2,4,6,-trimethylbenzoyl)-phosfineoxide; EC No.: 423-340-5; CAS No.: 162881-26-7

Weight fraction : $\geq 1 - < 5\%$

Classification 1272/2008 [CLP]: Skin Sens. 1; H317 Aquatic Chronic 4; H413

2-Propenoic acid; REACH registration No.: 01-211949003-49; EC No.: 629-850-6; CAS No.: 1245638-61-2

Weight fraction : $\geq 0.5 - < 1 \%$

Classification 1272/2008 [CLP]: Eye Dam. 1; H318 Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 2;

H411

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDY)SEBACAAT; CAS No.: 041556-26-7

Weight fraction: < 0,5 %

Classification 1272/2008 [CLP]: Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Page: 2 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 810 AS

Revision date : 09-11-2016 **Version (Revision) :** 1.1.0 (1.0.0)

Print date : 26-11-2018

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO2) Extinguishing powder Water mist

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Exposure to decomposition products may cause a health hazard. Use suitable breathing apparatus.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Avoid breathing vapours. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

Page: 3 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 810 AS

Revision date: 09-11-2016 **Version (Revision):** 1.1.0 (1.0.0)

Print date : 26-11-2018

7.1 Precautions for safe handling

Comply with the health and safety at work laws.

Protective measures

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Environmental precautions

Do not allow to enter drains or water courses.

Specific requirements or handling rules

Never use pressure to empty container.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8).

7.2 Conditions for safe storage, including any incompatibilities

Packaging materials

Always keep in containers of same material as the original one. Keep container tightly closed. No smoking. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Requirements for storage rooms and vessels

Only allow access to authorised staff.

Hints on joint storage

Do not store together with

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye/face protection

Use safety eyewear designed to protect against splash of liquids.

Skin protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hand protection

Use chemical-resistant gloves (according to EN 374).

By short-term hand contact: For short-term contact use gloves with adequate chemical protection, thickness \geq 0.2 mm, performance level \geq 1 (breakthrough time \geq 10 minutes).

By long-term hand contact: For prolonged and repeated contact use gloves with adequate chemical protection, thickness 0.4 mm, performance level 6 (breakthrough time ≥ 480 minutes).

Suitable material : NBR (Nitrile rubber)

Additional hand protection measures: Always ensure that gloves are free from defects and that they are stored and used correctly. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. After contact with skin, wash immediately with plenty of water and soap.

Respiratory protection

Not applicable.

Page: 4/8

according to Regulation (EC) No. 1907/2006 (REACH)



SolidLux Top Coat 810 AS Trade name:

Revision date: 09-11-2016 Version (Revision): 1.1.0 (1.0.0)

Print date: 26-11-2018

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Safety relevant basis data

Physical state: liauid Odeur: Typical paint odour. Odeur threshold: Unknown pH: No data available Melting point/melting range: No data available

Initial boiling point and boiling (1013 hPa) °C range:

Lower explosion limit: 0,6 Vol-%

Upper explosion limit : No data available

Vapour pressure: (50 °C / 122 °F) hPa Vapour density: No data available

Density: (20 °C / 68 °F) approx. 1,24 g/cm3

Solvent separation test: (20 °C / 68 °F) No data available Ignition temperature: No data available No data available **Decomposition temperature:**

Viscositeit KU: (20 °C / 68 °F) No data available

Flow time: (20 °C / 68 °F) 90 DIN-cup 4 mm Evaporation rate (n-butylacetate =

DIN 53170 1):

Flash point: 100 °C Technically impossible. Flammability:

Explosive properties: None

Solubility: Wt % None

Oxidising properties:

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Carbon monoxide Nitrogen oxides (NOx).

SECTION 11: Toxicological information

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of Regulation (EC) 1272/2008 and not classified.

11.1 Information on toxicological effects

Page: 5 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 810 AS

Revision date: 09-11-2016 **Version (Revision):** 1.1.0 (1.0.0)

Print date : 26-11-2018

The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

Do not allow to enter drains or water courses. Wastes and emptied containers should be classified in accordance with local/regional/national/international regulations.

13.1 Waste treatment methods

No information available.

13.2 Additional information

Empty containers must be scrapped or reconditioned. Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Page: 6 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 810 AS

Revision date: 09-11-2016 **Version (Revision):** 1.1.0 (1.0.0)

Print date : 26-11-2018

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

None

15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP]

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

ASTM = American Society of Testing and Materials (US)

CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)

DNEL = Derived No-Effect Level

DT50 = Time for 50% loss; half-life

EbC50 = Median effective concentration (biomass, e.g. of algae)

EC50 = Median effective concentration

EINECS = European Inventory of Existing Commercial Chemical Substan

ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)

ErC50 = Median effective concentration (growth rate, e.g. of algae)

EWC = European Waste Catalogue

IATA = International Air Transport Association

IC50 = Concentration that produces 50% inhibition

IMDG = International Maritime Dangerous Goods Code

IMO = International Maritime Organization

LC50 = Concentration required to kill 50% of test organisms

LD50 = Dose required to kill 50% of test organisms

LEL = Lower Explosive Limit/Lower Explosion Limit

LOAEL = Lowest observed adverse effect level

MRL = Maximum Residue Limit

NOAEL = No Observed Adverse Effect Level

NOEC = No observed effect concentration

NOEL = No Observable Effect Level

OEL = Occupational Exposure Limits

PBT = Persistent, Bioaccumulative or Toxic

PNEC = Previsible Non Effect Concentration

STEL = Short-Term Exposure Limit

TWA = Time-Weighted Average

vPvB = Very Persistent and Very Bioacccumulative

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Page: 7 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 810 AS

Revision date : 09-11-2016 **Version (Revision) :** 1.1.0 (1.0.0)

Print date : 26-11-2018

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 8 / 8