

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 910 AS  
Revision date : 08-03-2017  
Print date : 26-11-2018

Version (Revision) : 2.0.0 (1.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

SolidLux Top Coat 910 AS

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified use: Paints and lacquers, for further details check Product Data Sheet/ Label. Uses advised against: On substrates not mentioned in the Product Data Sheet/ Label.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier (manufacturer/importer/only representative/downstream user/distributor)

Lowland Coatings International B.V.

Street : Russenweg 14

Postal code/city : 8041 AL ZWOLLE

Telephone : +31 (0)38-4291200

Telefax : +31 (0)38-4210414

Contact : MSDS@wijzonol.com

### 1.4 Emergency telephone number

+31 (0)38-4291100(During office hours)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Exclamation mark (GHS07)

##### Signal word

Warning

##### Hazard components for labelling

HEXAMETHYLENE DIACRYLATE ; CAS No. : 13048-33-4

Trimethylolpropane Ethoxytriacylate ; CAS No. : 28961-43-5

Phenylbis(2,4,6,-trimethylbenzoyl)-phosfineoxide ; CAS No. : 162881-26-7

2-Propenoic acid ; CAS No. : 1245638-61-2

##### Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

##### Precautionary statements

P102 Keep out of reach of children.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** SolidLux Top Coat 910 AS  
**Revision date :** 08-03-2017  
**Print date :** 26-11-2018  
**Version (Revision) :** 2.0.0 (1.0.0)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P501 Dispose of contents/ container according to national/ international regulations.

## 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

3-methyl 1,5 pentanediol diacrylate ; EC No. : 264-727-7; CAS No. : 64194-22-5

Weight fraction :  $\geq 15 - < 20$  %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

HEXAMETHYLENE DIACRYLATE ; EC No. : 235-921-9; CAS No. : 13048-33-4

Weight fraction :  $\geq 5 - < 10$  %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319

Trimethylolpropane Ethoxytriacyrylate ; REACH registration No. : 01-2119489900-30 ; CAS No. : 28961-43-5

Weight fraction :  $\geq 5 - < 10$  %

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319

ACRYLIC RESIN ; CAS No. : --

Weight fraction :  $\geq 1 - < 5$  %

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Phenylbis(2,4,6,-trimethylbenzoyl)-phosfineoxide ; EC No. : 423-340-5; CAS No. : 162881-26-7

Weight fraction :  $\geq 1 - < 5$  %

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Chronic 4 ; H413

2-Propenoic acid ; REACH registration No. : 01-211949003-49 ; EC No. : 629-850-6; CAS No. : 1245638-61-2

Weight fraction :  $\geq 0,5 - < 1$  %

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDY)SEBACAAT ; CAS No. : 041556-26-7

Weight fraction :  $< 0,5$  %

Classification 1272/2008 [CLP] : Skin Sens. 1 ; H317 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do NOT use solvents or thinners.

#### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 910 AS  
Revision date : 08-03-2017  
Print date : 26-11-2018  
Version (Revision) : 2.0.0 (1.0.0)

and consult an ophthalmologist. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO<sub>2</sub>) Extinguishing powder Water mist

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Exposure to decomposition products may cause a health hazard. Use suitable breathing apparatus.

### 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire-fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

Due to the organic solvents' content of the mixture:

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Avoid breathing vapours. See protective measures under point 7 and 8.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean with detergents. Avoid solvent cleaners.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

##### Measures to prevent fire

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment should be protected to the appropriate standard. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** SolidLux Top Coat 910 AS  
**Revision date :** 08-03-2017  
**Print date :** 26-11-2018

**Version (Revision) :** 2.0.0 (1.0.0)

explosive mixtures with air.

#### **Environmental precautions**

Do not allow to enter drains or water courses.

#### **Specific requirements or handling rules**

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Avoid inhalation of dust from sanding. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container.

#### **Advices on general occupational hygiene**

Comply with the health and safety at work laws.

### **7.2 Conditions for safe storage, including any incompatibilities**

#### **Packaging materials**

Always keep in containers of same material as the original one.

#### **Hints on joint storage**

##### **Materials to avoid**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### **Further information on storage conditions**

Due to the organic solvents' content of the mixture: Keep container tightly closed. Keep away from sources of ignition - No smoking. Only allow access to authorised staff. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### **7.3 Specific end use(s)**

None

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

None

### **8.2 Exposure controls**

#### **Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### **Personal protection equipment**

##### **Eye/face protection**

Use safety eyewear designed to protect against splash of liquids.

##### **Skin protection**

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

##### **Hand protection**

Use chemical-resistant gloves (according to EN 374).

**By short-term hand contact :** For short-term contact use gloves with adequate chemical protection, thickness  $\geq$  0.2 mm, performance level  $\geq$  1 (breakthrough time  $\geq$  10 minutes).

**By long-term hand contact :** For prolonged and repeated contact use gloves with adequate chemical protection, thickness 0.4 mm, performance level 6 (breakthrough time  $\geq$  480 minutes).

**Suitable material :** NBR (Nitrile rubber)

**Additional hand protection measures :** Always ensure that gloves are free from defects and that they are stored and used correctly. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred. After contact with skin, wash immediately with plenty of water and soap.

##### **Respiratory protection**

Respiratory protection If workers are exposed to dust/ fumes/ aerosols in concentrations above the exposure limit, they must use appropriate, certified respirators(NEN-EN 140:1998/C1:2000, CE-marking) or independent breathing

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SolidLux Top Coat 910 AS  
Revision date : 08-03-2017  
Print date : 26-11-2018

Version (Revision) : 2.0.0 (1.0.0)

protection. The respiratory protection filter class must be at least suitable for the maximum concentration of the contamination (gas / vapor / dust particles) that may arise during use. We recommend using an AX filter according to EN 371 or EN14387. Always read the manufacturer's instructions before use. Pay attention to the wearing time limit of the respiratory mask! In case of exceedance of the specified maximum concentration, a compressed air mask must be used.

## Environmental exposure controls

Do not allow to enter drains or water courses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Safety relevant basis data

Physical state :				liquid	
Odeur:				Typical paint odour.	
Odeur threshold:				Unknown	
pH :				No data available	
Melting point/melting range :				No data available	
Initial boiling point and boiling range :	( 1013 hPa )				°C
Lower explosion limit :				0,6	Vol-%
Upper explosion limit :				No data available	
Vapour pressure :	( 50 °C / 122 °F )	<		3	hPa
Vapour density:					kPa
Density :	( 20 °C / 68 °F )	approx.		1,49	g/cm <sup>3</sup>
Solvent separation test :	( 20 °C / 68 °F )			No data available	
Ignition temperature :				No data available	
Decomposition temperature :				No data available	
Viscositeit KU :	( 20 °C / 68 °F )				KU
Flow time :	( 20 °C / 68 °F )	>		90	s
Evaporation rate (n-butylacetate = 1):					DIN-cup 4 mm DIN 53170
Flash point :		>		100	°C
Flammability:				Technically impossible.	
Explosive properties:				None	
Solubility:				No data available	
Oxidising properties:				None	

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

### 10.5 Incompatible materials

No information available.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** SolidLux Top Coat 910 AS  
**Revision date :** 08-03-2017  
**Print date :** 26-11-2018

**Version (Revision) :** 2.0.0 (1.0.0)

## 10.6 Hazardous decomposition products

No information available.

## SECTION 11: Toxicological information

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

### 11.1 Information on toxicological effects

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

## SECTION 12: Ecological information

There are no data available on the mixture itself. Do not allow to enter drains or water courses.

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

No information available.

### 12.6 Other adverse effects

No information available.

### 12.7 Additional ecotoxicological information

None

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Do not allow to enter drains or water courses. Empty containers must be scrapped or reconditioned. Not emptied containers are hazardous waste (waste code number 150110).

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** SolidLux Top Coat 910 AS  
**Revision date :** 08-03-2017  
**Print date :** 26-11-2018

**Version (Revision) :** 2.0.0 (1.0.0)

No dangerous good in sense of these transport regulations.

## 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

## 14.6 Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## 14.8 Additional information

### Air transport (ICAO-TI / IATA-DGR)

The "viscosity exemption" provision does not apply to air transport.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None

### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients

### 16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
ASTM = American Society of Testing and Materials (US)  
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)  
DNEL = Derived No-Effect Level  
DT50 = Time for 50% loss; half-life  
EbC50 = Median effective concentration (biomass, e.g. of algae)  
EC50 = Median effective concentration  
EINECS = European Inventory of Existing Commercial Chemical Substances  
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)  
ErC50 = Median effective concentration (growth rate, e.g. of algae)  
EWC = European Waste Catalogue  
IATA = International Air Transport Association  
IC50 = Concentration that produces 50% inhibition  
IMDG = International Maritime Dangerous Goods Code  
IMO = International Maritime Organization  
LC50 = Concentration required to kill 50% of test organisms  
LD50 = Dose required to kill 50% of test organisms  
LEL = Lower Explosive Limit/Lower Explosion Limit  
LOAEL = Lowest observed adverse effect level  
MRL = Maximum Residue Limit  
NOAEL = No Observed Adverse Effect Level  
NOEC = No observed effect concentration  
NOEL = No Observable Effect Level  
OEL = Occupational Exposure Limits  
PBT = Persistent, Bioaccumulative or Toxic  
PNEC = Predicted Non Effect Concentration  
STEL = Short-Term Exposure Limit  
TWA = Time-Weighted Average

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** SolidLux Top Coat 910 AS  
**Revision date :** 08-03-2017  
**Print date :** 26-11-2018

**Version (Revision) :** 2.0.0 (1.0.0)

---

vPvB = Very Persistent and Very Bioaccumulative

## 16.3 Key literature references and sources for data

None

## 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

## 16.6 Training advice

None

## 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---